

# AUTEL®

DISTRIBUTED BY  unipac

## A Revolution in Diagnostics

FAST | SMART | MOBILE | POWERFUL



+603 5569 0111   unipack1@unipac.com.my   Unipac Engineering (Malaysia)   unipac.engineering   unipac.engineering

No. 2, Jalan Jurubina U1/18, Hicom Glenmarie Industrial Park, Section U1, 40150 Shah Alam, Selangor D.E.

**MaxiIM IM508** ▾**OPERATING SYSTEM**

Android™ 4.4.4, KitKat

**PROCESSOR**Cortex-A9 processor  
(1.6 GHz)**MEMORY**

32 GB

**DISPLAY**7-inch LCD capacitive touch  
screen with 1024x600 resolution**CONNECTIVITY**

- Wi-Fi
- USB 2.0
- Mini USB: 2.0
- Micro SD card slot  
(supports up to 32GB)

**SENSORS**Ambient light sensor for  
brightness auto changing**POWER & BATTERY**

- 3.7 V/5000 mAh  
lithium-polymer battery
- Charges via 5 VDC  
power supply

**TESTED BATTERY LIFE**

Around 4.5 hours of continuous use

**NET WEIGHT**

885g(2.31lb.)

**BATTERY CHARGING INPUT**

5V/1.5A

**POWER CONSUMPTION**

500 mA (LCD on with default brightness, Wi-Fi on)@3.7 V

**OPERATING TEMP**

0 to 50°C (32 to 122°F)

**STORAGE TEMP**

-20 to 60°C (-4 to 140°F)

**OPERATING HUMIDITY**

5%-95% non-condensing

**MaxiIM IM608** ▾**OPERATING SYSTEM**

Android™ 4.4.2, KitKat

**PROCESSOR**1.3GHz Quad-core ARM Cortex-A7 +  
1.7GHz Dual-core ARM Cortex-A15**MEMORY**

2GB RAM &amp; 64GB On-board Memory

**DISPLAY**10.1-inch LED capacitive touch  
screen with 1920x1200 resolution**CONNECTIVITY**

- Wi-Fi (802.11 a/b/g/n/ac)
- USB: 2.0
- BT v.2.1 + EDR
- SD Card (Support up to 32GB)
- HDMI

**SENSORS**Gravity Accelerometer,  
Ambient Light Sensor (ALS)**POWER & BATTERY**

- 15000 mAh 3.8 V lithium-polymer battery
- Charging via 12 V AC/DC power supply with  
the temperature between 0°C and 45°C

**TESTED BATTERY LIFE**

-

**NET WEIGHT**

1.42 kg (3.13 lb.)

**INPUT VOLTAGE**

12 V (9-24 V)

**POWER CONSUMPTION**

6.5 W

**OPERATING TEMP**

0 to 50°C (32 to 122°F)

**STORAGE TEMP**

-20 to 60°C (-4 to 140°F)

**OPERATING HUMIDITY**

-